



# PRODUCT INFORMATION

FROM THE HOUSE OF PETRELPLUS INC.

## LITHEXPLUS - 3

### Product Description

Litexplus – 3 is a lithium soap grease formulated to provide outstanding mechanical stability. It is a multi purpose grease developed for use in a variety of operating conditions.

Litexplus – 3 grease provides excellent lubrication in both high and low temperature conditions. The product combines oxidation and corrosion inhibitors with high quality base stocks. It provides good resistance to water wash out and performs well under heavy load and high speed conditions. The product may be used within the range of temperatures defined by its minimum 200° C drop point and maintains excellent pump ability at low temperatures.

### Applications

**LITHEXPLUS – 3 IS RECOMMENDED FOR AUTOMOTIVE, INDUSTRIAL, MINING & AGRICULTURE APPLICATIONS.**

### Typical Properties

LITHEXPLUS - 3		
NLGI Grade	3	
Thickner Type	Lithium Soap	
Texture	Buttery	
Colour	Creamish White	
Worked Penetration (60 Strokes) @ 25% ° C	220-225	
Drop Point, ° C	200	
Mineral Oils, % wt	83	
Rust Test, D-1743	Pass	

**Available Packs : 18, 180 kg.**

### Performance Standard :- NLGI-3

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

The Material Safety Data Sheet (MSDS) are available upon request through our sales office.

\* All related specifications are meets or exceeds.

