

COPPER CONDUCTIVE GREASE SYNTHETIC COPPER CONDUCTIVE GREASE

Product Description

Electrically conductive Grease is used for improving electrical connections between sliding surfaces and parts. Conductive grease typically serves as a ground to provide excellent Electric channeling.

COPPER CONDUCTIVE GREASE is a premium low friction, electrically conductive grease based on micro size amorphous copper and other proprietary solid lubricants with non- melting high temperature apart from new generation oxidation and H2S inhibitors.

Applications & Usages

COPPER CONDUCTIVE GREASE is free from lead and aluminum and does not carbonize at high temperature up to 1100°C. It is recommended for stainless steel application above 360°C it performs well on similar and dissimilar metals. It provides rust, Corrosion protection while preventing seizing, galling, pitting, galvanic action and thread distortion. It is impervious to water, electrically conductive and offers protection from steam acids, caustic and harsh chemicals.

It is supplied ready to use to apply by brush, swab, or hand or grease gun. It is excellent for ground connections, rotating connections, rotary switches, variable capacitors, roller inductors, roller bearings, slip rings, slide connectors and potentiometers.

Benefits

- Reduces mechanical wear.
- Lubricates, reduces contact resistance, repels moisture, inhibits corrosion, and prevents static buildup.
- Ensures electrical contact between loose or vibrating parts.
- Improves electrical connections between irregular, pitted or corroded surfaces.
- Economical way to protect switches.

Uses

Clean and dry the surface before use. Apply a thin, even layer of grease using a spatula or other appropriate applicator

Typical Properties

COPPER CONDUCTIVE GREASE	
Appearance	Smooth Grease
Color	Dark Copper
Specific Gravity	1.2 ± 0.1
Kinematic Viscosity @40°C	1000
Operating Temperature	> 1100°C
Drop Point	None
NLGI	2
Worked Penetration	265-295
Copper Strip Corrosion, ASTM D 130	1a
4 Ball Weld Load ASTM D2509	> 800 Kg
Brush ability	Up to -12°C
Four ball Wear solids	0.4mm
Oil Separation	< 2.5 %
Friction Factor	1.1 (as per API RP 7A1)
Wear scar under 800N load	1.08
Coefficient of friction	0.10,
Press-Fit test m	
SKF EMCOR method	0
Degree of corrosion	

Available Packs: 1, 5, 18 and 180 Kg

Shelf Life – 36 Months from the Manufacturing month

* All related specifications are meets or exceeds.

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary slightly. The Material Safety Data Sheet (MSDS) are available upon request through our sales office.

1. PRODUCT AND COMPANY IDENTIFICATION

Product COPPER CONDUCTIVE GREASE
Supplier PETRELPLUS INC.

One World Center, Tower One, 9th Floor, Senapati Bapat Marg, Lower Parel, Mumbai-400013, Maharashtra.
Call # +91 22 6216 7072
(Monday to Friday)
Cell # +91 93522 25457
marketing@petrelplus.com
www.petrelplus.com

2. COMPOSITION

Composition of high-performance synthetic base oil and Proprietary additives.

3. HAZARDS IDENTIFICATION

Not classified as Hazardous.

4. FIRST-AID MEASURES

RESPIRATORY SYSTEM: Remove to fresh air and get medical attention.

INGESTION: Do not induce vomiting. Wash mouth out with water and obtain medical attention.

EYES: Rinse immediately with plenty of water for at least 10 minutes. Get Medical Attention.

SKIN: Remove contaminated clothing. Wash affected area with soap and water, get medical attention.

5. FIRE-FIGHTING METHODS

Foam, carbon dioxide or dry powder.

6. ACCIDENTAL RELEASE MEASURE

Contain and absorb in sand or earth. Ensure no material enters drains or water courses. Dispose of as solid waste in accordance with the relevant waste disposal regulations.

7. STORAGE AND HANDLING

Handling - At ambient temperatures wear gloves overalls and eye protection. The work area should be adequately ventilated. No eating drinking or smoking in the work area.

Storage - Store in delivery packs in a cool & dry place.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Standard:

The substance with exposure limit is: Notation 1: Exposure Standard: 2nd substance with exposure limit is: Notation 2:

PERSONAL PROTECTION

Respiratory Protection:

Type of Cartridge (if Applicable): Eye Protection: Safety Spectacles

Hand Protection: Gloves butyl or nitrile rubber

Industrial Hygiene: No eating drinking or smoking in the work area Ventilation: At room temperature handle in a well-ventilated area.

Use exhaust ventilation if exposure to flume or aerosol can occur.

PROTECTION AGAINST FIRE AND EXPLOSION

Combustible but not readily ignited. No explosion hazard.

EC SAFETY PHRASES: Not classified as hazardous.

9. TYPICAL PROPERTIES

Color	- Dark Copper
Drop Point °C	- None
Operating Temperature, °C	- > 1100
NLGI	-2

10. STABILITY AND REACTIVITY

HAZARDOUS REACTIONS

Comments

HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition produces noxious fumes.

11. TOXICOLOGICAL INFORMATION

LD50 Acute Oral Toxicity: > 5000:mg/Kg:Rat

LC50 Acute Inhalation: :mg/1

Eye Irritation: No: Rabbit

Skin Irritation: No.: Rabbit

Sensation: No

Further Information:

12. ECOLOGICAL INFORMATION

LC50 (96 Hour): mg/1

EC50 (24 Hour): mg/1

Biodegradability (Coupled units):

13. DISPOSAL CONSIDERATIONS

Solid material should be incinerated. Material absorbed on sand should be disposed of as solid waste.

14. TRANSPORT INFORMATION

IMDG No.: Not classified

Packing Groups: IATA-DGR Class No.: Not classified

TREMCARD: Not classified

RID/ADR Class No.: Not classified

Other Information

15. REGULATORY INFORMATION

Classification and labeling according to EC Directives 67/548

Not classified as hazardous. EC Risk Phrases

Not classified as hazardous. Other Hazardous

EC Safety Phrases

Not classified as hazardous

16. OTHER INFORMATION: PRODUCT SAFETY

For safety reasons, it is IMPERATIVE that customer: - Ensure that all those within their control who use the products are supplied with all relevant information contained within the Material Safety Data Sheet and Technical Bulletin concerning the applications for which the product is designed and any instructions or warning.

DISCLAIMER/USER'S RESPONSIBILITY: PETRELPLUS INC. Provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriate use.