



PRODUCT INFORMATION

FROM THE HOUSE OF PETRELPLUS INC.

LITHEXPLUS - 3

Product Description

Lithexplus – 3 is lithium soap grease formulated to provide outstanding mechanical stability. It is multipurpose grease developed for use in a variety of operating conditions.

Lithexplus –3 grease provides excellent lubrication in both high and low temperature conditions. The product combines oxidation and corrosion inhibitors with high quality base stocks. It provides good resistance to water wash out and performs well under heavy load and high speed conditions. The product may be used within the range of temperatures defined by its minimum 180° C drop point and maintains excellent pump ability at low temperatures.

Applications

LITHEXPLUS – 3 IS RECOMMENDED FOR, INDUSTRIAL, AUTOMOTIVE, STONE PROCESSING, MINING & AGRICULTURE APPLICATION.

Typical Properties

LITHEXPLUS - 3	
NLGI Grade	3
Color	Yellow
Thickener Type	Lithium Soap
Texture	Buttery
Kinematic Viscosity, @ 40° c	150
Kinematic Viscosity, @ 100° c	16.5
Worked Penetration (60 Strokes) @ 25% ° c	220-225
Drop Point, ° c	180
Mineral Oils, % wt	83
Rust Test, D-1743	Pass

Available Packs: 5, 18, 180 kg.

Performance Standard: - NLGI-3

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

The Material Safety Data Sheet (MSDS) are available upon request through our sales office

* All related specifications are meets or exceeds.

PETRELPLUS INC.
Level-13, R-Tech Park, Nirlon Knowledge Park,
Off Western Express Highway, Goregaon (e), Mumbai-400064
mail-marketing@petrelplus.com,
www.petrelplus.com