



SYNTHETIC BRAKE CALIPER GREASE

Product Description

PETRELPLUS SYNTHETIC BRAKE CALIPER GREASE is a Specially Blended High Temperature Grease with PTFE and synthetic Fluids for Brake Calipers. It resists moisture and will not washout.

Applications

- Caliper slides and pivot points
- Backing plates
- Caliper O rings
- Self-Adjusters
- Parking brake areas of lubrication
- Drum brake systems

Benefits

- Excellent water washout resistance.
- Compatible with majority of rubber and plastic compounds.
- High dielectric strength.
- Safe for caliper seals.
- Prevents rust and corrosion.
- Prevents Brake Noise and Vibrations.







Typical Properties

SYNTHETIC BRAKE CALIPER	
Base Oil	Synthetic
Structure	Smooth
Color	White
Temperature range, ⁰ C	-35 to 250°C
Density 20°C	9.63
Drop Point, ⁰ C, ASTM D 2265	250
Worked penetration DIN ISO 2137 at 25°C, 0.1 mm	270
Consistency DIN 51818 NLGI Grade	2
Viscosity cSt DIN 51562 @40°C	1000
@100°C	110

Available Packs: 1,5, 18, 50 & 180 Kg.

Shelf Life - 36 Months from the Manufacturing month.

* All related specifications are meets or exceeds. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly. The Material Safety Data Sheet (MSDS) are available upon request through our sales office.



Material Safety Data Sheet

PRODUCT AND COMPANY IDENTIFICATION 1.

Product SYNTHETIC BRAKE CALIPER GREASE Supplier PETRELPLUS INC. One World Center, Tower One, 9th Floor, Senapati Bapat Marg, Lower Parel, Mumbai-400013, Maharashtra. Call # +91 22 6216 7072 (Monday to Friday) Cell # +91 93522 25457 marketing@petrelplus.com www.petrelplus.com

COMPOSITION 2.

No harmful substances. Composition of Synthetic base oil, thickener with PTFE and Proprietary additives.

HAZARDS INDENTIFICATION 3.

Not classified as Hazardous.

FIRST-AID MEASURES 4.

RESPIRATORY SYSTEM: Remove to fresh air and get medical attention. **INGESTION:** Do not induce vomiting. Wash mouth out with water and obtain medical attention. EYES: Rinse immediately with plenty of water for at least 10 minutes. Get Medical Attention. **SKIN:** Remove contaminated clothing. Wash affected area with soap and water, get medical attention.

FIRE-FIGHTING METHODS 5.

Foam, carbon dioxide or dry powder.

ACCIDENTAL RELEASE MEASURE 6.

Contain and absorb in sand or earth. Ensure no material enters drains or water courses. Dispose of as solid waste in accordance with the relevant waste disposal regulations.

STORAGE AND HANDLING 7.

- At ambient temperatures wear gloves overalls and eye protection. The work area should be Handling adequately ventilated. No eating drinking or smoking in the work area. Storage

- Store in delivery packs in a cool & dry place.

EXPOSURE CONTROL / PERSONAL PROTECTION 8.

Exposure Standard:

The substance with exposure limit is: Notation 1: Exposure Standard: 2nd substance with exposure limit is: Notation 2:

PERSONAL PROTECTION

Respiratory Protection: Type of Cartridge (if Applicable): Eye Protection: Safety Spectacles Hand Protection: Gloves butyl or nitrile rubber Industrial Hygiene: No eating drinking or smoking in the work area Ventilation: At room temperature handle in a well-ventilated area. Use exhaust ventilation if exposure to flume or aerosol can occur.

PROTECTION AGAINST FIRE AND EXPLOSION

Combustible but not readily ignited. No explosion hazard. EC SAFETY PHRASES: Not classified as hazardous.

TYPICAL PROPERTIES 9.

Structure	- Soft -
Color	- White
Drop Point, ^o C	- 250
Temperature range, ⁰ C	- (- 35 to 250)

PETRELPLUS INC.



Material Safety Data Sheet

10. STABILITY AND REACTIVITY

HAZARDOUS REACTIONS **Comments** HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition produces noxious fumes.

11. TOXICOLOGICAL INFORMATION

LD50 Acute Oral Toxicity: > 5000:mg/Kg:Rat LC50 Acute Inhalation: :mg/1 Eye Irritation: No: Rabbit Skin Irritation: No.: Rabbit Sensation: No Further Information:

12. ECOLOGICAL INFORMATION

LC50 (96 Hour): mg/1 EC50 (24 Hour): mg/1 Biodegradability (Coupled units):

13. DISPOSAL CONSIDERATIONS

Solid material should be incinerated. Material absorbed on sand should be disposed of as solid waste.

14. TRANSPORT INFOMRATION

IMDG No.: Not classified Packing Groups: IATA-DGR Class No.: Not classified TREMCARD: Not classified RID/ADR Class No.: Not classified Other Information

15. REGULATORY INFORMATION

Classification and labeling according to EC Directives 67/548 Not classified as hazardous. EC Risk Phrases Not classified as hazardous. Other Hazardous EC Safety Phrases Not classified as hazardous

16. OTHER INFORMATION: PRODUCT SAFETY

For safety reasons, it is IMPERATIVE that customer: - Ensure that all those within their control who use the products are supplied with all relevant information contained within the Material Safety Data Sheet and Technical Bulletin concerning the applications for which the product is designed and any instructions or warning.

DISCLAIMER/USER'S RESPONSIBILITY: PETRELPLUS INC. Provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriate use.